

SEATTLE HOUSING AUTHORITY

HOUSE FIRE RENOVATION PHASE II

531 S DONOVAN ST  
SEATTLE WA 98108

FLOOR/CEILING/ROOF ASSEMBLY TYPES			FIRE RATING	S.T.C. RATING	THERMAL PROTECTION
No.	DIAGRAM	ASSEMBLY COMPONENTS	FIRE RATING REPORT NO.	S.T.C. RATING REPORT NO.	
R1		ASPHALT SHINGLE (CLASS A) VAPOR BARRIER MEMBRANE EXISTING PLYWOOD SHEATHING EXISTING ROOF TRUSSES R-49 UNFACED BATT INSULATION 5/8" GWB	N/A	N/A	R-49
F1		FINISH FLOORING PER PLAN EXISTING PLYWOOD SHEATHING EXISTING WOOD JOISTS R-30 HD UNFACED BATT INSULATION 5/8" TYPE 'X' GWB OR EXISTING SOFFIT AT EXTERIOR	-	-	R-30
F2		FINISH FLOORING PER PLAN EXISTING PLYWOOD SHEATHING EXISTING WOOD JOISTS 5/8" GWB	-	-	-

WALL ASSEMBLY TYPES			FIRE RATING	S.T.C. RATING	THERMAL PROTECTION
No.	DIAGRAM	ASSEMBLY COMPONENTS	FIRE RATING REPORT NO.	S.T.C. RATING REPORT NO.	
W1		EXISTING SIDING EXISTING WEATHER RESISTIVE BARRIER (WRB) EXISTING STRUCTURAL SHEATHING PER SHEARWALL SCHEDULE EXISTING 2x6 WOOD STUD R-21 KRAFT FACED BATT 5/8" GWB PVA VAPOR BARRIER PRIMER	N/A	N/A	R-21
W2		5/8" TYPE 'X' GWB EXISTING 2x6 WOOD STUD FRAMING R-21 KRAFT FACED BATT 5/8" GWB PVA VAPOR BARRIER PRIMER	N/A	N/A	R-21
W3		EXISTING SIDING EXISTING 2x6 WOOD STUD FRAMING	N/A	N/A	R-21
W4		5/8" GWB (USE MOISTURE RESISTANT DRYWALL AT TUB LOCATIONS) EXISTING 2x4 WOOD STUD FRAMING 5/8" GWB (USE MOISTURE RESISTANT DRYWALL AT TUB LOCATIONS)	N/A	N/A	-
W5		5/8" GWB (USE MOISTURE RESISTANT DRYWALL AT TUB LOCATIONS) EXISTING 2x6 WOOD STUD FRAMING R-21 UNFACED BATT INSULATION 5/8" GWB (USE MOISTURE RESISTANT DRYWALL AT TUB LOCATIONS)	N/A	N/A	-

REVISIONS/NOTES

NO	DATE	DESCRIPTION

PERMIT #: -

DRAWN: DD  
 CHECKED: JW  
 ISSUE DATE: 01.12.18  
 JOB NUMBER: 17039.00  
 TITLE:  
**ASSEMBLIES: WALL AND FLOOR**

AHJ STAMP